THE BANK OF MYSORE, LIMITED, BANGALORE.

Statement of the affairs of the Bank of Mysore, Limited, for the week ending 11th November 1937, published under Article 141 of the Articles of Association.

LIABILITIES	Rs.	ASSETS	Rs.
To Capital Receipts	20,00,000	By Cash in hand and at Bankers	42,13,851
,, Reserve Fund	25,00,000	,, Loans and Cash Credit Accounts	165,72,604
,, Public and other Deposits	263,55,417	,, Bills discounted	13,55,922
,, Sundries	4,97,774	,, Investments	83,62,205
		,, Balance at Agencies	
		,, Deed Stock	7,32,714
		,, Sundries	1,15,895
Total	313,53,191	Total	313,53,191

(Annas and pies omitted.)

BANGALORE,
Dated 16th November 1937.

F. L. PERADON,
Manager.

I, P. Ramachendra, intend to change my name as P. Ramachendra Sastry.

P. RAMACHANDRA SASTRY.

I, Doddaveerappa, intend to change my name as G. C. Doddaveerappa.

G. C. ದೊಡ್ಡವೀರಪ್ಪ.

I, B. N. Narasimha Murthy, intend to change my name as B. Narasimhamoorty.

B. NARASIMHAMURTY.

I, Vader Ramachendra, intend to change my name as V. Raghavendrachar.

V. RAGHAVENDRACHAR.

GOVERNMENT OF MYSORE, STORES PURCHASE COMMITTEE, BANGALORE.

No. S. P. C. 10348-78, *dated 9th November* 1937.

To

The Firms dealing in Wires and Cables.

Enquiry No. 2574.

FOREIGN MAINTENANCE MATERIALS FOR 1937-38. E.D. 592.

GENTLEMEN,

Please intimate your best present day prices and the earliest time of delivery for the cables specified below:—

1. 500 Ft.—Control cable for Station work, twin conductors each of size, 19—22 tinned copper wire (10 B. & S.) braided with differently coloured paraffin treated black and white coloured braids on the individual conductors with a tape and weather-proof braid overall, each conductor insulated with vulcanised rubber suitable for 600 volts pressure.

2. 1,200 Ft.—Do black, white, red and green coloured braids on the individual conductors with a tape and weather-proof braid overall, each conductor insulated with vulcanised rubber suitable for 600 volts pressure.

3. 200 Ft.—Do black, white, red, white and green white coloured braids, on the individual conductors with a tape and weather-proof braid overall, each conductor insulated with vulcanised rubber suitable for 600 volts pressure.

Note.—The individual conductor should be insulated with 3/64" high grade rubber suitable for a maximum of 600-volts pressure and should have different coloured cotton braids over each individual conductor for easy indentification, with a rubber filled tape overall, finished with a cotton braid impregnated with weather-proof compound.

You should give in your tenders detailed specifications for the above materials regarding the thickness of insulation, diameter, di-electric strength, etc.

The prices to be quoted should be for delivery c.i.f., Madras.

This enquiry will close on the 15th December 1937.